

PRODUCT DATA SHEET



Puridest PD 2 DG

With a design life of more than 15 years, LAUDA Puridest stills are one of the most reliable and most robust water treatment systems for laboratories in the world. The perfection of a centuries-old process guarantees high distillate quality on a long-term basis.

Technical Attributes	Puridest PD 2 DG
Ambient temperature min.	10 °C
Ambient temperature max.	40 °C
Distillation type	Double
Material	Glass
Production output	2 L/h
Conductivity at 25 °C	2.2 µS/cm
Cooling water flow rate	1.2 L/min
Dimensions (WxDxH) in mm	650x365x390
Weight	24.0 kg
Power consumption	2.9 kW

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser