


DURAN® Vacuum Desiccator

with screw thread outlet, type MOBILEX (GL 32), with screw cap from PBT




DURAN® desiccators completed with a desiccator lid and a screw cap.

Typical applications: drying of moist samples and storage of moisture-sensitive substances.

Cat. No.	DN	Thread	h (mm)	Volume approx. (mL)	ID Flange (mm)	Outer diameter (AD) Flange (mm)	Pack Unit
without porcelain plate							
247865707	150	32	239	2 400	172	215 ± 2	I
247866103	200	32	296	5 800	224	270 ± 2	I
247866609	250	32	344	10 500	274	320 ± 2	I
247866909	300	32	420	18 500	332	380 ± 2	I

DURAN® Desiccator

with flat flange, and knobbed lid, no connection



Made from DURAN® borosilicate glass 3.3. Components are vacuum tight. Spare parts such as lids and bases can be interchanged (observe DN).

Typical applications: drying of moist products and storage of moisture-sensitive substances.

Cat. No.	DN	h (mm)	Volume approx. (mL)	ID Flange (mm)	Outer diameter (AD) Flange (mm)	Pack Unit
247814603	100	187	700	119	153 ± 2	I
247815702	150	252	2 400	172	215 ± 2	I
247816107	200	309	5 800	224	270 ± 2	I
247816604	250	357	10 500	274	320 ± 2	I
247816904	300	433	18 500	332	380 ± 2	I